PSS- Production Screw Spiker







Key Features

The PSS - Production Screw Spiker includes the following key features:

- Enclosed, climate-controlled cab, with seating for two spiker operators and one feed-tray operator
- Four lag screw workheads, with guide roller and magazine feed
- · Manual pattern adjustment turnbuckle
- · Removable turntable
- John Deere Tier III diesel engine; Cummins Tier III engine available
- 24 VDC, circuit breaker-protected, electrical system
- Cobra brake shoes
- Four-wheel, dual-axle, chain-driven propulsion system
- Cab-controlled workhead power lock-ups
- Single, pressure-compensated, hydraulic pump
- · Joystick controls

Control your spike feed with manual or auto-load options.

Quickly adjust to different working conditions

Make a simple turnbuckle adjustment to adapt the gun spacing for different hole patterns. Or quickly add or remove clips to set the workhead to handle different rail heights. In addition, a removable turntable allows the PSS - Production Screw Spiker to easily reverse direction on the track.

High production levels

Use the dual-workhead mode to efficiently operate both the inside and outside workheads simultaneously. In addition, four workheads allow you to rapidly screw in all four lag screws at the same time.

Easily set drive levels

Adjust the drive height switch on the workhead from inside the cab - no tools required. In addition, fine-tune the drive depth with a simple dial setting.

Control spike feed manually or automatically

Decide how your lag screws feed into the jaws - select between manual load or auto-load options.

Quickly load spike kegs

Use the attached boom and winch to quickly load spike kegs onto the rear storage rack; the winch handles loads up to 300 lbs



Included boom and winch make it easy to load kegs onto the rear deck.



Seat-side controls allow quick switching between manual and automatic autofeed as well as single- and dual-workhead modes.



Intuitive joystick controls and excellent operator visibility allow increased precison during screw placement.

Ask us about...

Rebuild Programs

Are your maintenance-of-way machines getting older and less reliable? Nordco can rebuild virtually all maintenance-of-way equipment, regardless of original manufacturer, restoring your machines to like-new status.

Component Exchange Programs

Do you only need a replacement component, such as a workhead or axle, for your maintenance-of-way machine? You can order new or rebuilt components to be delivered directly to your shop or field operations.

Trade-In Programs

Interested in purchasing a new maintenance-of-way machine, but wondering what to do with your existing equipment? In many cases, you can trade in your current equipment for credit towards a new machine.

Rental Programs

Have a short-term need for a particular maintenance-of-way machine? Check our website for a current list of available rental equipment.

Parts Availability

Need parts for your maintenance-of-way machine? Contact our part experts at 1-800-647-1724, Monday through Friday, 7:30 a.m. to 5:00 p.m. US Central Time.

Want to ensure that you order the most essential parts to keep your maintenance-of-way machine operational? Check our website or ask your parts sales representative about the available critical component kits and basic spare part kits for your machine.

Not sure what parts to order for preventive maintenance or winterization? You'll find a large range of kits available - check our website or ask your parts sales representative.

Optional Equipment

Category	Option Type	Description
Cab	Cab accessories	Cab-controlled power locks, Cab pressurizer, cab window shades, engine-driven air conditioner
Spike Control	Spike accessories	Feeder swivel seat pedestal, screw spike feed warm-up kit, spike keg loading area curtain, steps and grab irons for bulkloading maintenance access
Repair & Maintenance	Corner-mounted jackstands	Holds the unit above the track to allow under-machine repairs
	Electric hydraulic tank fill system	Allows quick filling of hydraulic tank
	Spare hose tree	Stores extra hoses on the machine
	Remote coolant filter loops / Remote fluid drains	Allows quick filter/fluid maintenance
	Schroeder KF 30 case drain return filtration	Filters oil to remove engine wear-related metal filings
	Electric emergency pump	Allows workhead to be moved if engine fails
Other Accessories	Gauges and alarms	Fuel level site gauge, speedometer, hydraulic reservoir temperature gauge, low hydraulic oil/high hydraulic oil temperature alarm
	Lighting and mirrors	Heated outside mirrors and perimeter lighting package
	Storage	Additional book storage box, operator belongings box, track tool box
	Miscellaneous	"Danger Live Track" retractable belt, DOT reflective tape, extra parts/operations/maintenance manuals, rail sweeps, tow bar with D-handle hitch pins, windshield washer fluid tankand nozzles
	Turntable	Aluminum replacement for standard steel turntable, turntable warning light and buzzer

Product Specifications

Category	Specification	Value
General	Weight	26,750 lbs
	Length	25′ 8″
	Width	8′ 6″
	Height	9′ 10″
	Wheel base	163"
	Travel speed	25 mph (maximum)
Capacities	Fuel tank	120 gallons
	Hydraulic tank	115 gallons
Engine	Make/Model	John Deere 4045HF285, Tier III
	Туре	Four-cylinder, four-stroke
Hydraulic System	Make/Model	Vickers PVH series
	Control valves	Vickers manifolded
Electrical System	Battery	24 Vdc (dual 12V DC batteries), 1150 cold-cranking amps
Wheels	Size	3" standard
	Туре	Cast steel
Brakes	Туре	Four-wheel shoe-type, spring-actuated, hydraulic release

www.nordco.com

International Distributor American Equipment Company
4755 Technology Way, Suite 208
Boca Raton, FLORIDA USA 33431
Phone: 561-997-2080 / Fax: 561-997-2110

